

TA-TU



TA-TF

CHARACTERISTICS

- Easy and quick to install.
- Reusable.
- High resistance to weathering.
- Compatible with the most commonly used wires.
- Variety of formats.

APPLICATION EXAMPLES




1.RANGE

ITEM	CODE	PHOTO	DESCRIPTION	MATERIAL
1	TA-TU		Universal ratchet Wire diameters: 1,4 ÷ 2,2 1,8 ÷ 3,2 3,3 ÷ 4,2	
2	TA-TF		Endline ratchet Wire diameters: 1,8 ÷ 3,2	

2. INSTALLATION DATA

2.1 TA-TU

Universal ratchet



Material



Zamak

Installation Data

CODE	PHOTO	Wire diameters [mm]	Limit load [kg]	Loosening wrench*
TATU01		1,4 ÷ 2,2 (0,06" ÷ 0,09" / 17 SWG ÷ 14 SWG)	300	✓
TATU02		1,8 ÷ 3,2 (0,07" ÷ 0,13" / 15 SWG ÷ 10 SWG)	400	✗
TATU03		3,3 ÷ 4,2 (0,13" ÷ 0,17" / 10 SWG ÷ 7 1/2 SWG)	600	✓

* Including 5 loosening wrenchs without handle

2.2 TA-TF

Endline ratchet



Material



Zamak

Installation data

CODE	Wire diameters [mm]	Limit load [kg]	Loosening wrench *
TATF02	1,8 ÷ 3,2 (0,07" ÷ 0,13" / 15 SWG ÷ 10 SWG)	400	✗