



PVC-10B



PVC-10Z



PVC-20B



PVC-20Z



PVC-30



PVC-40B



PVC-40Z



PVC-50B



PVC-50Z



PVC-70



PVC-70TP



PVC-90



PVC-KOM10



PVC-VEK



PVC-VEK10



PVC-VEK13

CHARACTERISTICS

- Use in all kind of PVC Windows, doors and frames.
- Covering: zinc plated and zinc plated yellow passivated
- Versions for weather blinds of main manufacturers (Thyssen, Rehau, Veka and Kömmerling)

APPLICATIONS

- Fixing of U frame sections and metallic fittings to PVC.
- Fixing PVC pieces with each other.
- Fixing metallic reinforcements to PVC.
- Fixing PVC frames to the wall.
- Weather blinds and window drips, PVC carpentry repairs, etc.


BASE MATERIAL



APPLICATIONS EXAMPLES



1. SELECTION TABLE

SCREW	Head	Tip	Thread	Ø thread	Length	Recess	Covering	Application
PVC-10 	Countersunk Ø7.5	S, that allows perforation of plastics and PVCs	High-low	3.9	25 ÷ 45	Ph #2	Zinc plated/ Zinc plated yellow passivated	Fixing U frames with pilot hole to PVC profiles . Fixing metallic reinforcements with pilot hole to PVC profiles.
PVC-20 	Countersunk Ø7.5	S, that allows perforation of plastics and PVCs	40° Plastics	4.3	16 ÷ 55	Ph #2	Zinc plated/ Zinc plated yellow passivated	Fixing metallic reinforcements with pilot hole to PVC profiles. Use as reparation screw once PVC-10 has been released or screw is loose.
PVC-30 	Countersunk Ø7.5	S, that allows perforation of plastics and PVCs	40° Plastics	4.8	25 ÷ 38	Ph #2	Zinc plated yellow passivated	Fixing metallic reinforcements with pilot hole to PVC profiles. Use as reparation screw once PVC-10 and PVC-20 have been released or screw is loose.
PVC-40 	Countersunk Ø7.5	Self-drilling	60° Plastics	3.9	13 ÷ 38	Ph #2	Zinc plated/ Zinc plated yellow passivated	Fixing aluminium reinforcements ≤ 2.5 mm thick to PVC profiles, with total thickness (PVC + metallic reinforcements + intermediate cell) < 9 mm.
PVC-50 	Countersunk Ø7.5	Self-drilling	Metric	M4	13 ÷ 38	Ph #2	Zinc plated/ Zinc plated yellow passivated	To be used in very thin PVC profiles < 1 mm . Fixing aluminium reinforcements ≤ 2.5 mm thick to PVC profiles, with total thickness (PVC + metallic reinforcements + intermediate cell) < 9 mm.

SCREW	Head	Tip	Thread	Ø thread	Length	Recess	Covering	Application
PVC-70  PVC-70TP 	Countersunk special	C	60° Plastics	4.8	55 ÷ 95	Ph #2	Zinc plated yellow passivated	Fixing frames to walls. Joint of assemblies. Decorative caps.
PVC-90 	Low panhead with washer ø8.2 / 9.3	S, that allows perforation of plastics and PVCs	60° Plastics	3.5 / 4.0	10 ÷ 17	Ph #2	Zinc plated yellow passivated	PVC blind box. Fixing of non-countersunk metallic fittings to PVC.
PVC-KOM10 	Especial	S, that allows perforation of plastics and PVCs	60° Plastics	4.0	10	Ph #2	Zinc plated	Fixing of weather blinds and window drips to PVC profiles.
PVC-VEK 	Especial	S, that allows perforation of plastics and PVCs	60° Plastics	4.8	10	Ph #2	Zinc plated	Fixing of weather blinds and window drips to PVC profiles.
PVC-VEK10 	Especial	S, that allows perforation of plastics and PVCs	60° Plastics	4.0	10	Ph #2	Zinc plated yellow passivated	Fixing of weather blinds and window drips to PVC profiles.
PVC-VEK13 	Especial	Self-drilling	Self-drilling 60° Plastics	4.0	10	Ph #2	Zinc plated yellow passivated	Fixing of weather blinds and window drips to PVC profiles.